

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 548 088 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
29.06.2005 Bulletin 2005/26

(51) Int Cl.7: **C10G 67/04**

(21) Application number: **03293321.0**

(22) Date of filing: **23.12.2003**

(84) Designated Contracting States:
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IT LI LU MC NL PT RO SE SI SK TR**
Designated Extension States:
AL LT LV MK

(72) Inventors:
• **Adams, Nicholas James**
76650 Petit Couronne (FR)
• **Germaine, Gilbert Robert Bernard**
76650 Petit Couronne (FR)

(71) Applicant: **SHELL INTERNATIONALE RESEARCH
MAATSCHAPPIJ B.V.**
2596 HR Den Haag (NL)

(54) **Process to prepare a haze free base oil**

(57) Process to prepare a haze free base oil having a cloud point of below 0 °C and a kinematic viscosity at 100 °C of greater than 10 cSt by performing the following steps:

- (a) hydroisomerisation of a Fischer-Tropsch synthesis product,
- (b) isolating one or more fuel products and a residue having a 10 wt% recovery boiling point of above 500 °C and a wax content of greater than 50 wt%,
- (c) reducing the wax content of the residue to a val-

ue of below 50 wt% by contacting the feed with a hydroisomerisation catalyst under hydroisomerisation conditions, and

(d) solvent dewaxing the product of step (c) to obtain the haze free base oil.

EP 1 548 088 A1

Description

[0001] The invention relates to a process to prepare a haze free base oil having a kinematic viscosity at 100 °C of greater than 10 cSt from a Fischer-Tropsch wax.

[0002] WO-A-02070627 describes a process for preparing a base oil having a kinematic viscosity at 100 °C of 22 cSt from a heavy Fischer-Tropsch wax.

[0003] A problem of the prior art processes is that especially the base oils having a high viscosity often show a haze. This haze makes the process less suitable for some applications. However not all applications for this family of base oils require that a haze should be absent.

[0004] WO-A-03033622 describes a process wherein a haze free base oil is prepared from a Fischer-Tropsch product by removing the heaviest fraction, containing the haze precursors, by deep-cut distillation.

[0005] A disadvantage of the process according to WO A-03033622 is the deep cut distillation performed at a cut-off temperature of between 1150 and 1350 °F (621-732 °C). This is not only a technically difficult distillation step it also removes the valuable heavy base oil molecules together with the haze precursors.

[0006] The object of the present invention is a process to prepare haze free base oils in an efficient manner.

[0007] The following process achieves this object. Process to prepare a haze free base oil having a cloud point of below 0 °C and a kinematic viscosity at 100 °C of greater than 10 cSt by performing the following steps:

- (a) hydroisomerisation of a Fischer-Tropsch synthesis product,
- (b) isolating one or more fuel products and a residue having a 10 wt% recovery boiling point of above 500 °C and a wax content of greater than 50 wt%,
- (c) reducing the wax content of the residue to a value of below 50 wt% by contacting the feed with a hydroisomerisation catalyst under hydroisomerisation conditions, and
- (d) solvent dewaxing the product of step (c) to obtain the haze free base oil.

[0008] The process is advantageous because the wax feed used in step (a) contains the heaviest molecules as prepared in the Fischer-Tropsch synthesis. This is advantageous because it is now possible to prepare high viscosity grade base oils without having to perform a deep-cut distillation in order to remove possible haze-precursors. These advantages are even more pronounced when the feed to step (a), or (c), contains a large fraction of very high boiling compounds.

[0009] The Fischer-Tropsch synthesis product as used in step (a) can be obtained by well-known processes, for example the so-called commercial Sasol process, the Shell Middle Distillate Process or by the non-commercial Exxon process. These and other processes are for example described in more detail in EP-A-776959, EP-A-668342, US A-4943672, US-A-5059299,

WO-A-9934917 and WO-A-9920720.

[0010] More preferably the Fischer-Tropsch synthesis product comprises for at least 30 wt%, preferably at least 50 wt%, and more preferably at least 55 wt% of compounds having at least 30 carbon atoms. Furthermore the weight ratio of compounds having at least 60 or more carbon atoms and compounds having at least 30 carbon atoms of the Fischer-Tropsch product is at least 0.2, preferably at least 0.4 and more preferably at least 0.55.

[0011] Preferably the Fischer-Tropsch product comprises a C20+ fraction having an ASF-alpha value (Anderson-Schulz-Flory chain growth factor) of at least 0.925, preferably at least 0.935, more preferably at least 0.945, even more preferably at least 0.955.

[0012] The initial boiling point of the Fischer-Tropsch product may range up to 400 °C, but is preferably below 200 °C. Preferably any compounds having 4 or less carbon atoms and any compounds having a boiling point in that range are separated from a Fischer-Tropsch synthesis product before the Fischer-Tropsch synthesis product is used in said hydroisomerisation step.

[0013] Such a Fischer-Tropsch product can be obtained by any process, which yields a relatively heavy Fischer-Tropsch product. Not all Fischer-Tropsch processes yield such a heavy product. An example of a suitable Fischer-Tropsch process is described in WO-A-9934917 and in AU-A-698392. These processes may yield a Fischer-Tropsch product as described above.

[0014] The Fischer-Tropsch product will contain no or very little sulphur and nitrogen containing compounds. This is typical for a product derived from a Fischer-Tropsch reaction, which uses synthesis gas containing almost no impurities. Sulphur and nitrogen levels will generally be below the detection limits, which are currently 5 ppm for sulphur and 1 ppm for nitrogen.

[0015] The hydrocracking/hydroisomerisation reaction in step (a) is preferably performed in the presence of hydrogen and a catalyst, which catalyst can be chosen from those known to one skilled in the art as being suitable for this reaction. Catalysts for use in the hydroisomerisation typically comprise an acidic functionality and a hydrogenation/dehydrogenation functionality. Preferred acidic functionality's are refractory metal oxide carriers. Suitable carrier materials include silica, alumina, silica-alumina, zirconia, titania and mixtures thereof. Preferred carrier materials for inclusion in the catalyst for use in the process of this invention are silica, alumina and silica-alumina. A particularly preferred catalyst comprises platinum supported on a silica-alumina carrier. Preferably the catalyst does not contain a halogen compound, such as for example fluorine, because the use of such catalysts require special operating conditions and involve environmental problems. Examples of suitable hydrocracking/hydroisomerisation processes and suitable catalysts are described in WO-A-0014179, EP-A-532118, EP-A-666894 and the earlier referred to EP-A-776959.

[0016] Preferred hydrogenation/dehydrogenation functionality's are Group VIII metals, for example cobalt, nickel, palladium and platinum and more preferably platinum. In case of platinum and palladium the catalyst may comprise the hydrogenation/ dehydrogenation active component in an amount of from 0.005 to 5 parts by weight, preferably from 0.02 to 2 parts by weight, per 100 parts by weight of carrier material. In case nickel or cobalt is used a higher content will be present, optionally nickel is used in combination with copper. A particularly preferred catalyst for use in the hydroconversion stage comprises platinum in an amount in the range of from 0.05 to 2 parts by weight, more preferably from 0.1 to 1 parts by weight, per 100 parts by weight of carrier material. The catalyst may also comprise a binder to enhance the strength of the catalyst. The binder can be non-acidic. Examples are clays and other binders known to one skilled in the art.

[0017] In the hydroisomerisation the feed is contacted with hydrogen in the presence of the catalyst at elevated temperature and pressure. The temperatures typically will be in the range of from 175 to 380 °C, preferably higher than 250 °C and more preferably from 300 to 370 °C. The pressure will typically be in the range of from 10 to 250 bar and preferably between 20 and 80 bar. Hydrogen may be supplied at a gas hourly space velocity of from 100 to 10000 NI/V/hr, preferably from 500 to 5000 NI/V/hr. The hydrocarbon feed may be provided at a weight hourly space velocity of from 0.1 to 5 kg/V/hr, preferably higher than 0.5 kg/V/hr and more preferably lower than 2 kg/V/hr. The ratio of hydrogen to hydrocarbon feed may range from 100 to 5000 NI/kg and is preferably from 250 to 2500 NI/kg.

[0018] The conversion in the hydroisomerisation as defined as the weight percentage of the feed boiling above 370 °C which reacts per pass to a fraction boiling below 370 °C, is at least 20 wt%, preferably at least 25 wt%, but preferably not more than 80 wt%, more preferably not more than 70 wt%. The feed as used above in the definition is the total hydrocarbon feed fed to the hydroisomerisation, thus also any optional recycle to step (a).

[0019] In step (b) one or more distillate separations are performed on the effluent of the hydroisomerisation to obtain at least one middle distillate fuel fraction and the residue, which is to be used in step (c). Preferably the effluent of step (a) is subjected to an atmospheric distillation. The intermediate residue as obtained in such a distillation is subjected to a distillation performed at near vacuum conditions. This atmospheric bottom product or residue preferably boils for at least 95 wt% above 370 °C. The vacuum distillation is suitably performed at a pressure of between 0.001 and 0.1 bara. The residue as isolated in step (b) is obtained as the bottom product of such a vacuum distillation.

[0020] The wax content of the residue is above 50 wt% and more suitably above 70 wt%. The wax content as used in the description is measured according to the

following procedure. 1 weight part of the to be measured oil fraction is diluted with 4 parts of a (50/50 vol/vol) mixture of methyl ethyl ketone and toluene, which is subsequently cooled to -20 °C in a refrigerator. The mixture is subsequently filtered at -20 °C. The wax is removed from the filter and weighed. If reference is made to oil content a wt% value is meant which is 100% minus the wax content in wt%.

[0021] Step (c) may be performed using any hydroconversion process, which is capable of reducing the wax content of the residue. The wax content in the product of step (c) is preferably below 35 wt% and more preferably between 5 and 35 wt%, and even more preferably between 10 and 35 wt%. A minimal amount of wax is required in order to operate a solvent dewaxing step in an optimal manner. Preferably more than 50 wt% and more preferably more than 70 wt% of the intermediate product boils above the 10 wt% recovery point of the residue used in step (c).

[0022] A very suitable process is the hydroisomerisation process as described above for step (a). It has been found that the wax may be reduced to the desired level using such catalyst. By varying the severity of the process conditions as described above a skilled person will easily determine the required operating conditions to arrive at the desired wax conversion. However a temperature of between 300 and 330 °C and a weight hourly space velocity of between 0.1 and 0.5, more preferably between 0.1 and 0.3 kg of oil per litre of catalyst per hour (kg/V/hr) are especially preferred for optimising the oil yield.

[0023] A next suitable class of catalyst, which may be applied in step (c), is the class of dewaxing catalysts. The process conditions applied when using such catalysts should be such that a minimal wax content remains in the oil. In contrast typical catalytic dewaxing processes aim at reducing the wax content to almost zero.

[0024] The dewaxing catalyst which may be applied in step (c) suitably comprises a molecular sieve and optionally in combination with a metal having a hydrogenation function, such as the Group VIII metals. Molecular sieves, and more suitably molecular sieves having a pore diameter of between 0.35 and 0.8 nm have shown a good catalytic ability to reduce the wax content of the wax feed. Suitable zeolites are mordenite, beta, ZSM-5, ZSM-12, ZSM-22, ZSM-23, SSZ-32, ZSM-35 and ZSM-48. Another preferred group of molecular sieves are the silica-aluminaphosphate (SAPO) materials of which SAPO-11 is most preferred as for example described in US-A-4859311. ZSM-5 may optionally be used in its HZSM-5 form in the absence of any Group VIII metal. The other molecular sieves are preferably used in combination with an added Group VIII metal. Suitable Group VIII metals are nickel, cobalt, platinum and palladium. Examples of possible combinations are Pt/ZSM-35, Ni/ZSM-5, Pt/ZSM-23, Pd/ZSM-23, Pt/ZSM-48 and Pt/SAPO-11. Further details and examples of suitable molecular sieves and dewaxing conditions

are for example described in WO-A-9718278, US-A-4343692, US-A-5053373, US-A-5252527 and US-A-4574043.

[0025] A preferred class of molecular sieves are those having a relatively low isomerisation selectivity and a high wax conversion selectivity, like ZSM-5 and ferrierite (ZSM-35).

[0026] The dewaxing catalyst suitably also comprises a binder. The binder can be a synthetic or naturally occurring (inorganic) substance, for example clay, silica and/or metal oxides. Natural occurring clays are for example of the montmorillonite and kaolin families. The binder is preferably a porous binder material, for example a refractory oxide of which examples are: alumina, silica-alumina, silica-magnesia, silicazirconia, silicathoria, silica-beryllia, silica-titania as well as ternary compositions for example silicaalumina-thoria, silica-alumina-zirconia, silica-aluminamagnesia and silica-magnesia-zirconia. More preferably a low acidity refractory oxide binder material, which is essentially free of alumina, is used. Examples of these binder materials are silica, zirconia, titanium dioxide, germanium dioxide, boria and mixtures of two or more of these of which examples are listed above. The most preferred binder is silica.

[0027] A preferred class of dewaxing catalysts comprise intermediate zeolite crystallites as described above and a low acidity refractory oxide binder material which is essentially free of alumina as described above, wherein the surface of the aluminosilicate zeolite crystallites has been modified by subjecting the aluminosilicate zeolite crystallites to a surface dealumination treatment. A preferred dealumination treatment is by contacting an extrudate of the binder and the zeolite with an aqueous solution of a fluorosilicate salt as described in for example US-A-5157191 or WO-A-0029511. Examples of suitable dewaxing catalysts as described above are silica bound and dealuminated Pt/ZSM-5, silica bound and dealuminated Pt/ZSM-35 as for example described in WO-A-0029511 and EP-B-832171.

[0028] The conditions in step (c) when using a dewaxing catalyst typically involve operating temperatures in the range of from 200 to 500 °C, suitably from 250 to 400 °C. Preferably the temperature is between 300 and 330 °C. The hydrogen pressures in the range of from 10 to 200 bar, preferably from 40 to 70 bar, weight hourly space velocities (WHSV) in the range of from 0.1 to 10 kg of oil per litre of catalyst per hour (kg/l/hr), suitably from 0.1 to 1 kg/l/hr, more suitably from 0.1 to 0.3 kg/l/hr and hydrogen to oil ratios in the range of from 100 to 2,000 litres of hydrogen per litre of oil.

[0029] In step (d) the haze free oil is obtained by solvent dewaxing the product of step (c). Solvent dewaxing is well known to those skilled in the art and involves admixture of one or more solvents and/or wax precipitating agents with the base oil precursor fraction and cooling the mixture to a temperature in the range of from -10 °C to -40 °C, preferably in the range of from -20 °C to -35

°C, to separate the wax from the oil. The oil containing the wax is usually filtered through a filter cloth which can be made of textile fibres, such as cotton; porous metal cloth; or cloth made of synthetic materials. Examples of solvents which may be employed in the solvent dewaxing process are C3-C6 ketones (e.g. methyl ethyl ketone, methyl isobutyl ketone and mixtures thereof), C6-C10 aromatic hydrocarbons (e.g. toluene), mixtures of ketones and aromatics (e.g. methyl ethyl ketone and toluene), autorefrigerative solvents such as liquefied, normally gaseous C2-C4 hydrocarbons such as propane, propylene, butane, butylene and mixtures thereof. Mixtures of methyl ethyl ketone and toluene or methyl ethyl ketone and methyl isobutyl ketone are generally preferred. Examples of these and other suitable solvent dewaxing processes are described in Lubricant Base Oil and Wax Processing, Avilino Sequeira, Jr, Marcel Dekker Inc., New York, 1994, Chapter 7.

[0030] A preferred solvent dewaxing process for step (d) are the above described autorefrigerative solvents because use can be made of hydrocarbons which are prepared in the Fischer-Tropsch process or alternatively as separated from natural gas. More preferably the "propane dewaxing process" is used. More preferably cooling is performed by using liquid or gaseous nitrogen as obtained in an air separation process.

[0031] In step (d) also a wax is obtained. It has been found that such a wax is a relatively soft microcrystalline wax, which may be used for various purposes. The soft microcrystalline wax as obtained with the above process has preferably a congealing point as determined by ASTM D 938 of between 85 and 120 and more preferably between 95 and 120 °C and a PEN at 43 °C as determined by IP 376 of more than 0.8 mm and preferably more than 1 mm. The wax is further characterized in that it preferably comprises less than 1 wt% aromatic compounds and less than 10 wt% naphthenic compounds, more preferably less than 5 wt% naphthenic compounds. The mol percentage of branched paraffins in the wax is preferably above 33 and more preferably above 45 and below 80 mol% as determined by C13 NMR. This method determines an average molecular weight for the wax and subsequently determines the mol percentage of molecules having a methyl branch, the mol percentage of molecules having an ethyl branch, the mol percentage of molecules having a C3 branch and the mol percentage having a C4+ branch, under the assumption that each molecule does not have more than one branch. The mol% of branched paraffins is the total of these individual percentages. This method calculated the mol% in the wax of an average molecule having only one branch. In reality paraffin molecules having more than one branch may be present. Thus the content of branched paraffins determined by different method may result in a different value.

[0032] The oil content of the wax as determined by ASTM D 721 is typically below 10 wt% and more preferably below 6 wt%. If lower oil contents are desired it

may be advantageous to perform an additional de-oiling step. De-oiling processes are well known and are for example described in Lubricant Base Oil and Wax Processing, Avilino Sequeira, Jr, Marcel Dekker Inc., New York, 1994, pages 162-165. After de-oiling the wax preferably has a oil content of between 0.1 and 2 wt%. The lower limit is not critical. Values of above 0.5 wt% may be expected, but lower values can be achieved depending on the method in which the wax is obtained. Most likely the oil content will be between 1 and 2 wt%. The kinematic viscosity at 150 °C of the wax is preferably higher than 8 cSt and more preferably higher than 12 and lower than 18 cSt.

[0033] The haze free base oil will preferably have a kinematic viscosity at 100 °C of above 10 cSt, preferably above 14 cSt and typically below 30 cSt. The pour point is preferably below -18 °C, more preferably below -21 °C and even more preferably below -27 °C. The viscosity index is suitably above 120 and preferably above 130. A haze free base oil is determined by its cloud point. A haze free base oil according to this invention has a cloud point as determined by ASTM D2500 of below 0 °C, preferably below -10 °C and more preferably below -15 °C.

[0034] Because of these properties applicant has found that the base oil may be advantageously be used to prepare a lubricant composition which does not require a viscosity modifier (VM). Applicants further found that such a VISCOSITY MODIFIER-free lubricant may be obtained without having to add a poly-alpha olefin co-base oil as shown in WO-A-0157166. The invention is thus also directed to prepare a VM-free lubricant composition by blending a preferably Fischer-Tropsch derived and low viscosity base oil with the haze free base oil as obtained in step (c) and one or more additives. The low viscosity base oil preferably has a kinematic viscosity at 100 °C of less than 7 cSt. The haze free base oil preferably has a kinematic viscosity at 100 °C of more than 18 cSt.

[0035] Applicants found that by blending the haze free base oil with the lower viscosity grade base oil it is possible to achieve the properties of a SAE "xW-y" viscosity lubricant formulation without having to add a viscosity modifier. Applicants further found that when a viscosity modifier-free lubricant is used as motor engine lubricant in gasoline direct injection (GDI) engines no build up of residue on the back of the inlet valve tulip occurs, which would happen if a VM is present.

[0036] It has further been found that especially SAE "xW-y" viscosity lubricant formulations wherein y-x is greater or equal than 25 can be prepared without having to add a VM. Based on the teaching of WO-A-0157166 one would have expected that such formulations could only be prepared by having to add a VM.

[0037] The Fischer-Tropsch derived base oil having a kinematic viscosity at 100 °C of less than 7 cSt preferably has a pour point of less than -18 °C, more preferably less than -27 °C. The kinematic viscosity at 100 °C

is preferably greater than 3.5 cSt and more preferably between 3.5 and 6 cSt. The viscosity index (VI) is preferably greater than 120, more preferably greater than 130. The VI will typically be less than 160. The Noack volatility (according to CEC L40 T87) is preferably less than 14 wt%. The low viscosity component may any Fischer-Tropsch derived base oil as disclosed in for example EP-A-776959, EP-A-668342, WO-A-9721788, WO-0015736, WO-0014188, WO-0014187, WO-0014183, WO-0014179, WO-0008115, WO-9941332, EP-1029029, WO-0118156 and WO-0157166.

Claims

1. Process to prepare a haze free base oil having a cloud point of below 0 °C and a kinematic viscosity at 100 °C of greater than 10 cSt by performing the following steps:
 - (a) hydroisomerisation of a Fischer-Tropsch synthesis product,
 - (b) isolating one or more fuel products and a residue having a 10 wt% recovery boiling point of above 500 °C and a wax content of greater than 50 wt%,
 - (c) reducing the wax content of the residue to a value of below 50 wt% by contacting the feed with a hydroisomerisation catalyst under hydroisomerisation conditions, and
 - (d) solvent dewaxing the product of step (c) to obtain the haze free base oil.
2. Process according to claim 1, wherein the wax content in step (c) is reduced to below 35 wt%.
3. Process according to claim 2, wherein the wax content in the product of step (c) is between 10 and 35 wt%.
4. Process according to any one of claims 1-3, wherein the Fischer-Tropsch synthesis product has a weight ratio of compounds having at least 60 or more carbon atoms and compounds having at least 30 carbon atoms in the Fischer-Tropsch product is at least 0.2 and wherein at least 30 wt% of compounds in the Fischer-Tropsch synthesis product have at least 30 carbon atoms.
5. Process according to claim 4, wherein at least 50 wt% of compounds in the Fischer-Tropsch product have at least 30 carbon atoms.
6. Process according to any one of claims 4-5, wherein the weight ratio of compounds having at least 60 or more carbon atoms and compounds having at least 30 carbon atoms in the Fischer-Tropsch product is at least 0.4.

7. Process according to any one of claims 1-6, wherein the 10 wt% recovery boiling point of the residue as isolated in step (b) is between 500 and 550 °C.
8. Process according to any one of steps 1-7, wherein more than 50 wt% of the product of step (c) boils above the 10 wt% recovery point of the residue used as feed in step (c). 5
9. Process according to claim 8, wherein more than 70 wt% of the product of step (c) boils above the 10 wt% recovery point of the residue used as feed in step (c). 10
10. Process according to any one of claims 1-9, wherein the hydroisomerisation catalyst used in step (c) is a substantially amorphous based catalyst comprising a silica-alumina carrier and a noble or non-noble Group VIII metal. 15
11. Process according to any one of claims 1-9, wherein the hydroisomerisation catalyst used in step (c) is a molecular sieve based catalyst and a noble or non-noble Group VIII metal. 20
12. Process to prepare a lubricant composition not containing a viscosity modifier additive by blending a low viscosity base oil with the haze free base oil as obtained in step (d) of the process as described in claims 1-11 and one or more additives. 25
- 30

35

40

45

50

55



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number

EP 03 29 3321

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	EP 0 471 524 A (EXXON RESEARCH ENGINEERING CO) 19 February 1992 (1992-02-19) * page 3, lines 2-7 and lines 37-53; page 4, lines 1-17; page 6, lines 25-27; example; figure *	1-12	C10G67/04
A,D	EP 0 776 959 A (SHELL INT RESEARCH) 4 June 1997 (1997-06-04) * the whole document *	1-12	
A	WO 02 099014 A (BENARD GERARD ; DUPREY ERIC (FR); SHELL INT RESEARCH (NL); VAN VEEN) 12 December 2002 (2002-12-12) * the whole document *	1-12	
A	WO 99 41335 A (EXXON RESEARCH ENGINEERING CO ; MURPHY WILLIAM JOHN (US); CODY IAN) 19 August 1999 (1999-08-19) * the whole document *	1-12	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			C10G C10M
The present search report has been drawn up for all claims			
Place of search MUNICH		Date of completion of the search 26 March 2004	Examiner Cagnoli, M
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

1
EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 03 29 3321

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

26-03-2004

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
EP 0471524	A	19-02-1992	CA	2047923 A1	15-02-1992
			EP	0471524 A1	19-02-1992
			JP	3032051 B2	10-04-2000
			JP	4233995 A	21-08-1992

EP 0776959	A	04-06-1997	EP	0776959 A2	04-06-1997
			EP	1365005 A1	26-11-2003
			AU	705415 B2	20-05-1999
			AU	7198896 A	05-06-1997
			CA	2191290 A1	29-05-1997
			CN	1167811 A ,B	17-12-1997
			JP	9221685 A	26-08-1997
			SG	74001 A1	18-07-2000
			TW	416981 B	01-01-2001
			ZA	9609906 A	28-05-1997

WO 02099014	A	12-12-2002	CA	2449348 A1	12-12-2002
			WO	02099014 A2	12-12-2002
			EP	1392799 A2	03-03-2004

WO 9941335	A	19-08-1999	AU	742858 B2	17-01-2002
			AU	3290599 A	30-08-1999
			CA	2320113 A1	19-08-1999
			EP	1062306 A1	27-12-2000
			JP	2002503755 T	05-02-2002
			WO	9941335 A1	19-08-1999
			US	2003226785 A1	11-12-2003
			US	6620312 B1	16-09-2003
